

Microphone capsule		MK 102		MK 221		MK 211		MK 301	
Load impedance		100 k Ω	1 k Ω	100 k Ω	1 k Ω	100 k Ω	1 k Ω	100 k Ω	1 k Ω
Max. SPL	0.5% THD		136 dB		136 dB		147 dB		156 dB
	1.0% THD	137 dB		138 dB		149 dB		159 dB	
Max. U _{OUT}	0.5% THD		6.3 V _{rms}		6.2 V _{rms}		6.2 V _{rms}		6.5 V _{rms}
	1.0% THD	7.0 V _{rms}		8.0 V _{rms}		8.0 V _{rms}		9.0 V _{rms}	
Gain	10 Hz	-0.3 dB	-3.2 dB	-0.8 dB	-3.6 dB	-0.8 dB	-3.6 dB	-2.0 dB	-4.9 dB
	1 kHz	-0.2 dB	-1.0 dB	-0.7 dB	-1.5 dB	-0.7 dB	-1.5 dB	-2.0 dB	-2.8 dB
	20 kHz	-0.2 dB	-1.0 dB	-0.7 dB	-1.5 dB	-0.7 dB	-1.5 dB	-2.0 dB	-2.8 dB
	40 kHz					-0.7 dB	-1.5 dB		
	100 kHz							-1.8 dB	-2.6 dB
Inherent noise	A-weighted	3.5 μ V	3.2 μ V	5.6 μ V	5.1 μ V	3.6 μ V	3.3 μ V	3.7 μ V	3.4 μ V
	CCIR-weighted	14.0 μ V	13.0 μ V	24.7 μ V	22.6 μ V	15.5 μ V	14.1 μ V	14.0 μ V	12.8 μ V
	IEC 268-4	11 dB(A)		15 dB(A)		22 dB(A)		36 dB(A)	
	CCIR 468-4	23 dB(A)		28 dB(A)		35 dB(A)		48 dB(A)	